

CLAIM OR CLAIMS

WHAT IS CLAIMED IS:

1. A method of setting up a communication procedure between instances,
5 with one instance being a protocol tester, comprising the steps of:

selecting the instances that take part in the communication procedure;

selecting a protocol layer on the basis of the communication
procedure;

10 selecting abstract communication interfaces of the protocol layer for
the communication procedure;

selecting communication data; and

15 automatically setting up through the protocol tester the communication
procedure on the basis of the selections made in the above selecting steps,
with the abstract communication interfaces selecting and/or the
communication data selecting steps being made graphically and parameters
selectable during these steps being assigned description files that are used
in the setting up step to set up the communication procedure.

2. The method as recited in claim 1 wherein the instances selecting step
20 comprises the step of selecting the instances graphically, and/or the protocol
layer selecting step comprises the step of selecting the protocol layer
graphically, and the parameters selectable in these steps being assigned
description files that are used in the setting up step.

3. The method as recited in claims 1 or 2 wherein the abstract communication interfaces comprise Service Access Points (SAPs).

4. The method as recited in claim 3 wherein the communication data
5 comprise at least one type selected from the group consisting of Protocol Data Units (PDUs) and Abstract Service Primitives (ASPs).

5. The method as recited in claims 1 or 2 wherein the communication data
10 comprise at least one type selected from the group consisting of Protocol Data Units (PDUs) and Abstract Service Primitives (ASPs).

6. The method as recited in claim 1 wherein the communication data selecting step comprises the steps of:

graphically selecting a data format; and

15 graphically setting up a communication sequence between the selected instances.

7. The method as recited in claim 6 wherein the graphically setting up step comprises the step of entering source code.

20 8. A protocol tester comprising:

means for selecting instances taking part in a communication procedure, one of the instances being the protocol tester;

25 means for selecting a protocol layer on the basis of the communication procedure;

means for selecting abstract communication interfaces of the protocol layerfor the communication procedure;

means for selecting communication data; and

means for automatically setting up the communication procedure

5 through the protocol tester on the basis of the selections of the various selecting means, with the abstract communication interfaces selecting means and/or the communication data selecting means being graphical selecting means and parameters selected by the various selecting means being assigned description files that are used in the automatically setting up means
10 for setting up the communication procedure.

9. The protocol tester as recited in claim 8 wherein the instances selecting means and/or the protocol layer selecting means comprise graphical selecting means and the parameters selected by these selecting means are
15 assigned description files that are used in the automatically setting up means.

10. The protocol tester as recited in claims 8 or 9 wherein the abstract communication interfaces comprise Service Access Points (SAPs).

20 11. The protocol tester as recited in claim 10 wherein the communication data comprises one type selected from the group consisting of Protocol Data Units (PDUs) and Abstract Service Primitives (ASPs).

12. The protocol tester as recited in claim 11 further comprising means for entering source codes.

13. The protocol tester as recited in claim 8 wherein all parameters selected
5 by all the selecting means are assigned description files that are used by the setting up means.